



07410 ROOF & WALL PANELS
FIBERGLASS REINFORCED PLASTIC (FRP) PANEL SPECIFICATION
FRP GUTTER & DOWNSPOUT SYSTEM**

PAGE 1

(** insert into standard panel specification as section 2.01 Material, subsection G. or appropriate subsection)

G. FRP Gutter & Downspout System

1. The gutter and downspout system shall be fiberglass reinforced plastic by Resolite, a Stabilit America Co., 285 Industrial Drive, Moscow, TN 38057, Ph: 888-737-6548.
2. Glass reinforcement for the gutter and downspout system shall include unidirectional filaments to provide high tensile and flexural properties and overall section stiffness. In addition, continuous strand mat shall be included to contribute to the transverse properties of the gutter and downspout sections. Glass content shall be a minimum of 40% by weight.
3. Resin shall be high quality isophthalic halogenated polyester equivalent to Hetron 99P, having a flame spread classification of 25* or less. Additional protection shall be provided with the use of UV stabilizers.
4. Finish shall be smooth.
5. Color shall be _____ (Stone White, Gray or Beige) and coloring shall be achieved through the use of pigments impregnated through the entire profile.
6. Configuration of the gutter and the downspout shall be as shown on the drawings.
7. Gutter and downspout system shall be installed in accordance with the manufacturer's recommendations.

*Resolite advises that the numerical flame spread classification is not intended to reflect hazards presented by this or any other material under actual fire conditions.

----- END OF SPECIFICATION -----