

# UV STABILIZED SKYLIGHT & SIDELIGHT PANELS

D. N





Resolite is a premier North America manufacturer of Fiberglass Reinforced Panels for exterior skylight and sidelight applications such as post frame buildings, pre-engineered metal buildings and greenhouses. Polylit panels are available in a variety of popular profiles which makes it a perfect choice where natural lighting is preferred.

# **EXCELLENT QUALITY**

- Years of dependable performance
- Designed to fit most applications
- UV Stabilized Polyester Unsaturated Resin

### **CHEMICAL RESISTANCE**

- Mildew and stain resistant
- Corrosion resistant
- Minimum maintenance and never needs painting

#### LOW COST INSTALLATION

- Easy to handle and install
- No special tools needed
- Wide range of available sizes and weights

#### **HIGHLY IMPACT RESISTANT**

- · Extremely high strength to weight ratio
- Tough surface that resists shattering, scratches and abrasions

#### **GENERAL INFORMATION**

• Conforms to ASTM D-3841-97 (2008-2014) Standard Specifications for Glass Fiber **Reinforced Polyester Plastic Panels** 

## STORAGE RECOMMENDATIONS

- Store panels indoors in a cool, dry, well ventilated area
- Panels should be stacked on skids not more than 250 sheets high
- Do not stack anything on top of panels

## 1-1/4" Width: 26"





2-1/2" x 1/2" Wide Width: 52-5/8", 51-1/2", 34", 26" Coverage: 50-21/32", 48", 32", 24"



52-5/8"

2-1/2" x 1/2" Narrow Width: 26" Coverage: 24"

**38" Granite City Strong** 



38-178 36 21/32



Width: 38-1/8"

Coverage: 36"









New Grand Rib III Width: 37-3/4" Length: 36"

#### **R-Panel**

Width: 38" Length: 36"

**Ridge Cap** Width: 24"

**U-Panel** 

Width: 38" Coverage: 36"























www.resolite.com 285 Industrial Drive, Moscow, TN 38057

Width: 38-3/8" Coverage: 36"

Wheeling Channel Drain 2000

Wheeling 38 Channel Drain Width: 38-1/4" Coverage: 35-7/8"

Wheeling Channel Drain Width: 38-1/4"

Coverage: 36"

#### **Century Drain**

Width: 37-3/4" Coverage: 35-7/8"

#### Delta Rib

Width: 26-1/4" Coverage: 24"

Pro IIA Width: 38-1/4" Coverage: 36"

**Flat Rolls** Width: 48" Length: 50' Rolls